

1/4 Multisocket

p. 12.4

								
80191 Pg. 12.4	80192 Pg. 12.4	80193 Pg. 12.4	80221 Pg. 12.4	80221AC Pg. 12.4	80222 Pg. 12.5	80222AC Pg. 12.5	80223 Pg. 12.5	80223AC Pg. 12.5
								
80291 Pg. 12.5	80292 Pg. 12.5	80293 Pg. 12.6	80271 Pg. 12.6	80271AC Pg. 12.6	80272 Pg. 12.6	80272AC Pg. 12.6	80273 Pg. 12.6	

3/8 Multisocket

p. 12.8

						
80194 Pg. 12.8	80195 Pg. 12.8	80231 Pg. 12.8	80231AC Pg. 12.8	80232 Pg. 12.8	80232AC Pg. 12.9	80298 Pg. 12.9

1/4 Multisocket - Stainless Steel

p. 12.11

							
60191 Pg. 12.11	60192 Pg. 12.11	60221 Pg. 12.11	60222 Pg. 12.11	63190 Pg. 12.12	63192 Pg. 12.12	63260 Pg. 12.12	63262 Pg. 12.12

AC Mini

p. 12.14

			
80111 Pg. 12.14	80112 Pg. 12.14	80211 Pg. 12.14	80212 Pg. 12.14

Industrial

p. 12.16

							
80121 Pg. 12.16	80122 Pg. 12.16	80221 Pg. 12.16	80222 Pg. 12.16	80131 Pg. 12.17	80132 Pg. 12.17	80231 Pg. 12.17	80232 Pg. 12.17

Safety Couplers - Blow Guns

p. 12.21

								
80621 Pg. 12.21	80622 Pg. 12.21	621 Pg. 12.21	622 Pg. 12.21	80221AC Pg. 12.22	80222AC Pg. 12.22	80225AC Pg. 12.22	8B121 8B122 Pg. 12.22	361-362 Pg. 12.24

QUICK DISCONNECT COUPLERS



Quick Couplers



TECHNICAL CHARACTERISTICS



MULTISOCKET


Universal quick disconnect

One socket for 3 different plugs

It's a fact that there are various Quick-Disconnect plugs available on the market today. In most cases, each plug needs a specific coupler that is not interchangeable.

To get around this issue, Aignep is proud to offer to its customers a practical and cost-effective solution.

MULTISOCKET is a universal coupler that works with the 3 main types of QD plugs.




Reference Standard

1907/2006
REACH


2011/65/CE
RoHS

PED
2014/68/UE

SILICON
FREE




1/4 INDUSTRIAL



1:1

DN
5.5 mm


ARO



1:1

DN
5.5 mm

TRU-FLATE



1:1

DN
5 mm



Component Parts and Materials

- 1 Nickel Plated Brass Body
- 2 420 Stainless Steel Ball
- 3 Nickel Plated Brass Guide Ring
- 4 NBR O-Ring Seal
- 5 302 Stainless Steel Ring Nut Spring
- 6 NBR O-Ring Seal
- 7 Nickel Plated Brass Sleeve
- 8 NBR O-Ring Seal
- 9 Nickel Plated Brass Shutter
- 10 302 Stainless Steel Shutter Spring
- 11 Nickel Plated Brass Coupler



Pressure Rating

0 ~ 232 PSI
0 bar ~ 16 bar
0 MPa ~ 1.6 MPa

Maximum static pressure

507 PSI
35 bar
3.5 MPa



Temperatures

NBR
-4° F ~ 176° F
-20° C ~ 80° C

FKM on request
14° F ~ 392° F
-10° C ~ 200° C



Threads

NPTF



Media

- Compressed air
- For other fluids, consult the technical department Aignep.



Flow Rate


CFM (NI/min)

Plug	87 psi Δ 14.5	87 psi Δ 7.2	87 psi Δ 0 (Exhaust Free)
80220	38.8 (1100)	28.25 (800)	52.97 (1500)
80270	45.9 (1300)	35.31 (1000)	58.27 (1650)
80290	22.95 (650)	16.95 (480)	38.8 (1100)

1/4" MULTISOCKET

80191


1/4" MALE NPTF



Part No.	A NPTF	B	C	D	CH
80191-04	1/4	.512 (13)	2.126 (54)	.945 (24)	.827 (21)
80191-06	3/8	.512 (13)	2.126 (54)	.945 (24)	.827 (21)
80191-08	1/2	.669 (17)	2.303 (58,5)	.945 (24)	.945 (24)

80192


1/4" FEMALE NPTF



Part No.	A NPTF	B	C	D	CH
80192-04	1/4	.533 (13,5)	2.126 (54)	.945 (24)	.827 (21)
80192-06	3/8	.533 (13,5)	2.126 (54)	.945 (24)	.827 (21)
80192-08	1/2	.689 (17,5)	2.323 (59)	.945 (24)	.945 (24)

80193

1/4" BARB




Part No.	A	C	D	CH
80193-04	1/4	2.382 (60,5)	.945 (24)	.827 (21)
80193-06	3/8	2.402 (61)	.945 (24)	.827 (21)
80193-08	1/2	2.402 (61)	.945 (24)	.866 (22)

1/4" INDUSTRIAL

80221


1/4" INDUSTRIAL MALE



Part No.	A NPTF	B	C	CH
80221-04	1/4	.512 (13)	1.634 (41,5)	.669 (17)
80221-06	3/8	.512 (13)	1.634 (41,5)	.748 (19)
80221-08	1/2	.669 (17)	1.811 (46)	.866 (22)

80221AC

1/4" INDUSTRIAL MALE (STEEL)



Part No.	A NPTF	B	C	CH
80221AC-04	1/4	.512 (13)	1.634 (41,5)	.669 (17)
80221AC-06	3/8	.512 (13)	1.634 (41,5)	.748 (19)
80221AC-08	1/2	.669 (17)	1.811 (46)	.866 (22)

HARDENED STEEL

80222


1/4" INDUSTRIAL FEMALE



Part No.	A NPTF	B	C	CH
80222-04	1/4	.531 (13,5)	1.535 (39)	.669 (17)
80222-06	3/8	.531 (13,5)	1.535 (39)	.787 (20)
80222-08	1/2	.689 (17,5)	1.693 (43)	.944 (24)

80222AC

1/4" INDUSTRIAL FEMALE (STEEL)




Part No.	A NPTF	B	C	CH
80222AC-04	1/4	.531 (13,5)	1.535 (39)	.669 (17)
80222AC-06	3/8	.531 (13,5)	1.535 (39)	.866 (22)
80222AC-08	1/2	.689 (17,5)	1.693 (43)	.944 (24)

HARDENED STEEL

80223


1/4" INDUSTRIAL BARB



Part No.	A	C	D
80223-04	1/4	1.713 (43,5)	.472 (12)
80223-08	1/2	1.811 (46)	.629 (16)

80223AC

1/4" INDUSTRIAL BARB (STEEL)




Part No.	A	C	D
80223AC-04	1/4	1.713 (43,5)	.472 (12)

HARDENED STEEL

TRU FLATE

80291


1/4" TRU-FLATE MALE



Part No.	A NPTF	B	C	CH
80291-04	1/4	.512 (13)	1.457 (37)	.669 (17)
80291-06	3/8	.512 (13)	1.457 (37)	.748 (19)
80291-08	1/2	.669 (17)	1.634 (41,5)	.866 (22)

80292

1/4" TRU-FLATE FEMALE




Part No.	A NPTF	B	C	CH
80292-04	1/4	.531 (13,5)	1.358 (34,5)	.669 (17)
80292-06	3/8	.531 (13,5)	1.358 (34,5)	.787 (17)
80292-08	1/2	.689 (17,5)	1.516 (38,5)	.945 (24)

80293

1/4" TRU-FLATE BARB

Part No.	A	B	D
80293-04	1/4	1.634 (41,5)	.472 (12)
80293-06	3/8	1.634 (41,5)	.551 (14)
80293-08	1/2	1.634 (41,5)	.787 (20)




ARO

80271

1/4" ARO MALE

Part No.	A NPTF	B	C	CH
80271-04	1/4	.511 (13)	1.574 (40)	.669 (17)
80271-06	3/8	.511 (13)	1.574 (40)	.748 (19)
80271-08	1/2	.669 (17)	1.771 (45)	.866 (22)




80271AC

1/4" ARO MALE (STEEL)

Part No.	A NPTF	B	C	CH
80271AC-04	1/4	.511 (13)	1.574 (40)	.669 (17)


HARDENED STEEL



80272

1/4" ARO FEMALE

Part No.	A NPTF	B	C	CH
80272-04	1/4	.531 (13,5)	1.496 (38)	.669 (17)
80272-06	3/8	.531 (13,5)	1.496 (38)	.787 (20)
80272-08	1/2	.689 (17,5)	1.653 (42)	.945 (24)




80272AC

1/4" ARO FEMALE (STEEL)

Part No.	A NPTF	C	D	CH
80272AC-04	1/4	.531 (13,5)	1.496 (38)	.669 (17)


HARDENED STEEL



80273

1/4" ARO BARB

Part No.	A	B	D
80273-04	1/4	1.673 (42,5)	.472 (12)
80273-08	1/2	1.791 (45,5)	.787 (20)





TECHNICAL CHARACTERISTICS



MULTISOCKET


Universal quick disconnect

One socket for 2 different plugs

It's a fact that there are various Quick-Disconnect plugs available on the market today. In most cases, each plug needs a specific coupler that is not interchangeable.

To get around this issue, Aignep is proud to offer to its customers a practical and cost-effective solution.

MULTISOCKET is a universal coupler that works with the 2 main types of QD plugs.



Pressure Rating

0 ~ 232 PSI
0 bar ~ 16 bar
0 MPa ~ 1.6 MPa

Maximum static pressure

507 PSI
35 bar
3.5 MPa



Temperatures

NBR
-4° F ~ 176° F
-20° C ~ 80° C

FKM on request
14° F ~ 392° F
-10° C ~ 200° C




Reference Standard

1907/2006
REACH ✓


2011/65/CE
RoHS ✓

PED
2014/68/UE

SILICON
FREE




3/8 INDUSTRIAL



1:1
DN
9 mm

3/8 TRU-FLATE



1:1
DN
9 mm



Component Parts and Materials

- 1 Nickel Plated Brass Body
- 2 420 Stainless Steel Ball
- 3 Nickel Plated Brass Guide Ring
- 4 NBR O-Ring Seal
- 5 302 Stainless Steel Ring Nut Spring
- 6 NBR O-Ring Seal
- 7 Nickel Plated Brass Sleeve
- 8 NBR O-Ring Seal
- 9 Nickel Plated Brass Shutter
- 10 302 Stainless Steel Shutter Spring
- 11 Nickel Plated Brass Coupler



Threads

NPTF



Media

- Compressed air
- For other fluids, consult the technical department Aignep.



Flow Rate

CFM (NI/min)

Plug	87 psi Δ 14.5	87 psi Δ 7.2	87 psi Δ 0 (Exhaust Free)
80230	88.2 (2500)	72.3 (2050)	116.5 (3300)
80297	88.2 (2500)	72.3 (2050)	116.5 (3300)


3/8" MULTISOCKET

80194

3/8" MALE NPTF



Part No.	A NPTF	B	C	D	CH
80194-06	3/8	.512 (13)	2.342 (59,5)	1.102 (28)	.945 (24)
80194-08	1/2	.669 (17)	2.500 (63,5)	1.102 (28)	.945 (24)




80195

3/8" FEMALE NPTF



Part No.	A NPTF	B	C	D	CH
80195-06	3/8	.531 (13,5)	2.362 (60)	1.102 (28)	.945 (24)
80195-08	1/2	.689 (17,5)	2.520 (64)	1.102 (28)	.945 (24)




3/8" INDUSTRIAL

80231

3/8" INDUSTRIAL MALE

Part No.	A NPTF	B	C	CH
80231-06	3/8	.512 (13)	1.732 (44)	.748 (19)
80231-08	1/2	.669 (17)	1.909 (48,5)	.866 (22)




80231AC

3/8" INDUSTRIAL MALE (STEEL)

Part No.	A NPTF	B	C	CH
80231AC-06	3/8	.512 (13)	1.732 (44)	.748 (19)
80231AC-08	1/2	.669 (17)	1.909 (48,5)	.866 (22)


HARDENED STEEL



80232


3/8" INDUSTRIAL FEMALE

Part No.	A NPTF	B	C	CH
80232-06	3/8	.531 (13,5)	1.634 (41,5)	.787 (20)
80232-08	1/2	.669 (17)	1.791 (45,5)	.866 (22)



80232AC

3/8" INDUSTRIAL FEMALE (STEEL)




Part No.	A NPTF	B	C	CH
80232AC-06	3/8	.531 (13,5)	1.634 (41,5)	.787 (20)
80232AC-08	1/2	.689 (17,5)	1.791 (45,5)	.945 (24)

HARDENED STEEL

3/8" TRU FLATE

80298

3/8" TRU-FLATE FEMALE




Part No.	A NPTF	B	C	CH
80298-06	3/8	.531 (13,5)	1.654 (42)	.787 (20)
80298-08	1/2	.689 (17,5)	1.811 (46)	.866 (24)



TECHNICAL CHARACTERISTICS



MULTISOCKET
Universal quick disconnect



Reference Standard


1907/2006

REACH✓


2011/65/CE

RoHS✓

PED
2014/68/UE

SILICON
FREE



1/4 INDUSTRIAL



1:1

DN
5.5 mm


ARO



1:1

DN
5.5 mm

EUROPEAN



1:1

DN
7.8 mm


Pressure Rating

0 PSI ~ 232 PSI

0 bar ~ 16 bar

0 MPa ~ 1.6 MPa

Maximum static pressure

507 PSI

35 bar

3.5 MPa



Component Parts and Materials

- 1 316 Stainless Steel Body
- 2 420 Stainless Steel Ball
- 3 316 Stainless Steel Guide Ring
- 4 FKM O-Ring Seal
- 5 302 Stainless Steel Ring Nut Spring
- 6 FKM O-Ring Seal
- 7 316 Stainless Steel Sleeve
- 8 FKM O-Ring Seal
- 9 316 Stainless Steel Shutter
- 10 302 Stainless Steel Shutter Spring
- 11 316 Stainless Steel Coupler



Temperature Rating

FKM

5° F ~ 392° F

-15° C ~ 200° C



Threads

NPTF
BSPP


Media

- Compressed air
- Fluid for food and chemical industry compatible with all components.



Flow Rate


CFM (NI/min)

Plug	87 psi Δ 14.5	87 psi Δ 7.2	87 psi Δ 0 (Exhaust Free)
1/4 INDUSTRIAL	88.2 (2500)	72.3 (2050)	116.5 (3300)
EUROPEAN	53.32 (1510)	42.38 (1200)	79.45 (2250)

1/4" MULTISOCKET STAINLESS STEEL

60191


1/4" MALE NPTF 316L
(STAINLESS)



Part No.	A NPTF	B	C	D	CH
60191-04	1/4	.511 (13)	2.086 (53)	.945 (24)	.827 (21)

60192


1/4" FEMALE NPTF 316L
(STAINLESS)



Part No.	A NPTF	B	C	D	CH
60192-04	1/4	.533 (13,5)	2.066 (52,5)	.945 (24)	.827 (21)

60221


1/4 INDUSTRIAL MALE 316L (STAINLESS)



Part No.	A NPTF	B	C	CH
60221-04	1/4	.512 (13)	1.633 (41)	.669 (17)

60222

1/4 INDUSTRIAL FEMALE 316L (STAINLESS)



Part No.	A NPTF	B	C	CH
60222-04	1/4	.533 (13,5)	1.535 (39)	.669 (17)


63 Series

63190

1/4" MALE 316L
(STAINLESS)

Universal quick disconnect

Universal thread

Document 1



Part No.	A	B	C	D	CH
63190-04	1/4	.276 (7)	1.969 (50)	.945 (24)	.827 (21)
63190-06	3/8	.295 (7,5)	1.988 (50,5)	.945 (24)	.827 (21)
63190-08	1/2	.354 (9)	2.047 (52)	.945 (24)	.827 (21)

63192

1/4" FEMALE 316L
(STAINLESS)

Universal quick disconnect

Universal thread


Document 1


Part No.	A BSPP	B	C	D	CH
63192-04	1/4	.433 (11)	2.028 (51,5)	.945 (24)	.827 (21)
63192-06	3/8	.453 (11,5)	2.047 (52)	.945 (24)	.827 (21)
63192-08	1/2	.591 (15)	2.224 (56,5)	.945 (24)	.945 (24)

63260 DN 7.8

MALE PLUG
EUROPEAN PROFILE

Universal thread


Document 1


Part No.	A	B	C	CH
63260-04	1/4	.276 (7)	1.319 (33,5)	.669 (17)
63260-06	3/8	.295 (7,5)	1.339 (34)	.748 (19)
63260-08	1/2	.354 (9)	1.417 (36)	.945 (24)

63262 DN 7.8

FEMALE PLUG
EUROPEAN PROFILE

Universal thread

Document 1


Part No.	A BSPP	B	C	CH
63262-04	1/4	.433 (11)	1.299 (33)	.669 (17)
63262-06	3/8	.453 (11,5)	1.319 (33,5)	.748 (19)
63262-08	1/2	.591 (15)	1.457 (37)	.945 (24)



TECHNICAL CHARACTERISTICS






Reference Standard

1907/2006
REACH ✓

2011/65/CE
RoHS ✓

PED
2014/68/UE

SILICON
FREE


1:1



Pressures

0 PSI ~ 232 PSI
0 bar ~ 16 bar
0 MPa ~ 1.6 MPa

Maximum static pressure

507 PSI
35 bar
3.5 MPa


Component Parts and Materials

- 1 Nickel Plated Brass Body
- 2 420 Stainless Steel Ball
- 3 Nickel Plated Brass Sleeve
- 4 NBR O-Ring Seal
- 5 302 Stainless Steel Ring Nut Spring
- 6 Nickel Plated Brass Shutter
- 7 NBR O-Ring Seal
- 8 NBR O-Ring Seal
- 9 302 Stainless Steel Shutter Spring
- 10 Nickel Plated Brass Coupler



Temperature Rating

NBR

-4° F ~ 176° F	FKM <i>on request</i>
-20° C ~ 80° C	14° F ~ 392° F
	-10° C ~ 200° C



Threads

NPTF



Media

- Compressed air
- For other fluids, consult the technical department Aignep.



Flow Rate


CFM (NI/min)

87 psi Δ 14.5	87 psi Δ 7.2	87 psi Δ 0 (Exhaust Free)
8.48 (240)	6.71 (190)	11.3 (320)

80111

AC MINI MALE


Part No.	A NPTF	B	C	D	CH
80111-02	1/8	.335 (8,5)	1.496 (38)	.709 (18)	.630 (16)
80111-04	1/4	.512 (13)	1.673 (42,5)	.709 (18)	.630 (16)
80111-06	3/8	.512 (13)	1.673 (42,5)	.709 (18)	.751 (19)



80112

AC MINI FEMALE


Part No.	A NPTF	B	C	D	CH
80112-02	1/8	.335 (8,5)	1.457 (37)	.709 (18)	.630 (16)
80112-04	1/4	.531 (13,5)	1.614 (41)	.709 (18)	.669 (17)
80112-06	3/8	.531 (13,5)	1.614 (41)	.709 (18)	.787 (20)



80211

AC MINI MALE PLUG


Part No.	A NPTF	B	C	CH
80211-02	1/8	.335 (8,5)	1.122 (28,5)	.551 (14)
80211-04	1/4	.512 (13)	1.319 (33,5)	.669 (17)
80211-06	3/8	.512 (13)	1.319 (33,5)	.748 (19)



80212


AC MINI FEMALE PLUG

Part No.	A NPTF	B	C	CH
80212-02	1/8	.374 (9,5)	1.063 (27)	.551 (14)
80212-04	1/4	.531 (13,5)	1.220 (31)	.669 (17)
80212-06	3/8	.531 (13,5)	1.220 (31)	.787 (20)





TECHNICAL CHARACTERISTICS



Pressure Rating

0 PSI ~ 232 PSI
0 bar ~ 16 bar
0 MPa ~ 1.6 MPa

Maximum static pressure

507 PSI
35 bar
3.5 MPa



Temperature Rating

NBR
-4° F ~ 176° F
-20° C ~ 80° C

FKM *on request*
14° F ~ 392° F
-10° C ~ 200° C



Media

• Compressed air
For other fluids, consult the technical department Aignep.



Reference Standard


1907/2006
REACH ✓

2011/65/CE
RoHS ✓

PED
2014/68/UE


SILICON
FREE

1/4 INDUSTRIAL




1:1

DN
5.5 mm




3/8 INDUSTRIAL



1:1

DN
9 mm



Component Parts and Materials

- 1 Nickel Plated Brass Body
- 2 Nickel Plated Brass Sleeve
- 3 420 Stainless Steel Ball
- 4 Nickel Plated Brass Guide Ring
- 5 NBR O-Ring Seal
- 6 302 Stainless Steel Ring Nut Spring
- 7 Nickel Plated Brass Shutter
- 8 NBR O-Ring Seal
- 9 NBR O-Ring Seal
- 10 302 Stainless Steel Shutter Spring
- 11 Nickel Plated Brass Coupler



Threads

NPTF



Flow Rate


CFM (NI/min)

Plug	87 psi Δ 14.5	87 psi Δ 7.2	87 psi Δ 0 (Exhaust Free)
1/4 IND.	38.8 (1100)	28.25 (800)	52.97 (1500)
3/8 IND.	88.28 (2500)	72.39 (2050)	116.53 (3300)

1/4" INDUSTRIAL INTERCHANGE

80121


1/4" INDUSTRIAL MALE



Part No.	A NPTF	B	C	D	CH
80121-04	1/4	.512 (13)	2.224 (56,5)	.945 (24)	.827 (21)
80121-06	3/8	.512 (13)	2.224 (56,5)	.945 (24)	.827 (21)
80121-08	1/2	.669 (17)	2.402 (61)	.945 (24)	.945 (24)

80122


1/4" INDUSTRIAL FEMALE



Part No.	A NPTF	B	C	D	CH
80122-04	1/4	.531 (13,5)	2.205 (56)	.945 (24)	.827 (21)
80122-06	3/8	.531 (13,5)	2.205 (56)	.945 (24)	.827 (21)
80122-08	1/2	.689 (17,5)	2.421 (61,5)	.945 (24)	.945 (24)

80221


1/4" INDUSTRIAL MALE PLUG



Part No.	A NPTF	B	C	CH
80221-04	1/4	.512 (13)	1.634 (41,5)	.669 (17)
80221-06	3/8	.512 (13)	1.634 (41,5)	.748 (19)
80221-08	1/2	.669 (17)	1.811 (46)	.866 (22)

80222

1/4" INDUSTRIAL FEMALE PLUG




Part No.	A NPTF	B	C	CH
80222-04	1/4	.531 (13,5)	1.535 (39)	.669 (17)
80222-06	3/8	.531 (13,5)	1.535 (39)	.787 (20)
80222-08	1/2	.689 (17,5)	1.693 (43)	.944 (24)

3/8" INDUSTRIAL INTERCHANGE

80131


3/8" INDUSTRIAL MALE



Part No.	A NPTF	B	C	D	CH
80131-06	3/8	.512 (13)	2.362 (60)	1.102 (28)	.945 (24)
80131-08	1/2	.669 (17)	2.4802 (63)	1.102 (28)	.945 (24)

80132


3/8" INDUSTRIAL FEMALE



Part No.	A NPTF	B	C	D	CH
80132-06	3/8	.531 (13,5)	2.343 (59,5)	1.102 (28)	.945 (24)
80132-08	1/2	.689 (17,5)	2.500 (63,5)	1.102 (28)	.945 (24)

80231


3/8" INDUSTRIAL MALE PLUG



Part No.	A NPTF	B	C	CH
80231-06	3/8	.512 (13)	1.732 (44)	.748 (19)
80231-08	1/2	.669 (17)	1.909 (48,5)	.866 (22)

80232

3/8" INDUSTRIAL FEMALE PLUG



Part No.	A NPTF	B	C	CH
80232-06	3/8	.531 (13,5)	1.634 (41,5)	.787 (20)
80232-08	1/2	.689 (17,5)	1.791 (45,5)	.945 (24)

1/4" Basic size: Industrial									
AIGNEP	MILTON	AMFLO	ARO	COIL HOSE	DIXON	NAPA	PARKER	FOSTER	TOMCO
80192-04	715	C20-AU	MSCF22-000	150	DC20	90-670	B23	2803	M184
80191-04	716	C21	MSCM22-000	152	DC21	90-672	B22	2903	M181
80193-04	717	C20-42	MSCH22-000	153	DC2042	90-671	B20-3B	3603	M186
80193-06	717-6	C20-44	MSCH23-000		DC2044			3703	M187
80192-06	718	C20-23	MSCF23-000	151	DC2023	90-667	B23E	3203	M185
80191-06	719	C21-03	MSCM23-000	155	DC2103	90-657	B22E	3303	M182
80221-04	727	CP21	23902-210	1501	DCP21	90-674	H2C	10-3	1804
80222-04	728	CP20	23902-200	1502	DCP2021	90-676	H3C	11-3	1805
80222-06	732	CP20-23	23902-300	1505	DCP2023	90-659	H3C-E	15-3	1807
80221-06	733	CP21-03	23902-310	1503	DCP2103	90-677	H2C-E	14-3	1806
80223-04	736	CP21-42	23902-220	1506	DCP2142	90-673	H8C	16-3	1824
80223-06	736-6	CP21-44	23902-420	1508	DCP2144		H9C	17-3	1826
80192-04	745								UC2-16
80191-04	746								UC2-15
80192-04	755	C40B	MSCF22-X00		DCB20	90-615	B33		
80191-04	756	C41B	MSCM22-X00		DCB21	90-617	B32		
80193-04	1717-4	C20-42L	MSCP22-000				B20-3BP		
80193-06	1717-6	C20-44L	MSCP23-000				B20-5BP		
1/4" Basic size: ARO									
AIGNEP	MILTON	AMFLO	ARO	COIL HOSE	DIXON	NAPA	PARKER	FOSTER	TOMCO
80192-04	775	C38,C46	210	140	DC38	90-613	B53	210-3303	A100
80191-04	776	C37,C45	210-212		DC37		B50	210-3103	A101
80193-04	776-4	C38-42	210-022		DC3842	90-679	B50-3BP	210-3603	A104
80193-06	776-6	C38-44	210-215		DC3844		B50-5BP	210-3703	A105
80271-04	777	CP37	2608	1401	DCP37	90-618	A2C	210-10	200
80273-04	777-4	CP37-42	3946	1406	DCP3742		A8C	210-16	400
80273-06	777-6	CP37-44	22238		DCP3744			210-17	500
80272-04	778	CP38	2609	1402	DCP38	90-620	A3C	210-11	300
1/4" Basic size: TRU-FLATE									
AIGNEP	MILTON	AMFLO	ARO	COIL HOSE	DIXON	NAPA	PARKER	FOSTER	TOMCO
80291-04	783	CP1	TFPM22-000	1601	DCP1	90-628	2C	TF10	2154
80293-04	783-4	CP1-42	TFPH22-000	1606	DCP142	90-630	8C	TF16	2164
80293-06	783-6	CP1-44	TFPH23-000	1608	DCP143	90-626	9C	TF17	2166
80292-04	784	CP2	TFPH22-000	1602	DCP2	90-600	3C	TF11	2155
80192-04	785	C2	TFCF22-000	160	DC2	90-610	B13	TF3003	A2184
80191-04	786	C1	TFCM22-000	162	DC1	90-607	B12	TF3103	A2181
80193-04	786-4	C2-42	TFCH22-000	163	DC242	90-611	B10-3B	TF3603	A2186
80193-06	786-6	C2-44	TFCH23-000	166	DC244	90-609	B10-5B	TF3703	A2188
80192-06	788	C2-23	TFCF23-000					TF3203	A2185
80191-06	789	C1-03	TFCM23-000		DC103			TF3303	A2182
3/8" Basic size: Industrial									
AIGNEP	MILTON	AMFLO	ARO	COIL HOSE	DIXON	NAPA	PARKER	FOSTER	TOMCO
80195-06	1835	C26	MSCF33-000	580	DC26	90-680	25	4204	T420
80194-06	1836	C25	MSCM33-000	581	DC25	90-682	24	4304	T430
80195-08									T440
80194-08									T450
80231-06	1837	CP25	23903-310	5801	DCP25	90-683	H2E	42-4	T42
80232-06	1838	CP26	23903-300	5802	DCP26	90-681	H3E	43-4	T43
80231-08									T44
80232-08									T45
3/8" Basic size: TRU-FLATE									
AIGNEP	MILTON	AMFLO	ARO	COIL HOSE	DIXON	NAPA	PARKER	FOSTER	TOMCO
80195-06	1805	C6	TFCF33-000	590	DC6	90-654	15	5005	PT420
80194-06	1806	C5	TFCM33-000	591	DC5	90-656	14	5105	PT430
80281-06	1807	CP5	TFPM33-000	5901	DCP5	90-658	2E	TF42	PT42
80282-06	1808	CP6	TFPF33-000	5902	DCP6	90-660	3E	TF43	PT43

Safety Couplers

QUICK DISCONNECT SAFETY COUPLERS




Connect the plug



Quick coupling
is working



Push the sleeve
ahead and leave the hand



Air is exhausting
completely



Remove the plug




TECHNICAL CHARACTERISTICS



Reference Standard

1907/2006 REACH✓	2011/65/CE RoHS✓	PED 2014/68/UE	SILICON FREE	ISO 4414
---------------------	---------------------	-------------------	-----------------	-------------



Pressure Rating

Vacuum ~ 217 PSI
-0.99 bar ~ 15 bar
-0.099 MPa ~ 1.5 MPa



Temperature Rating

-4° F ~ 176° F
-20° C ~ 80° C



Media

- Compressed air



Threads

Parallel gas in conformity with ISO 228 Class A



Component Parts and Materials

- 1 Nickel Plated Brass Coupler
- 2 Nickel Plated Brass Shutter
- 3 Nickel Plated Brass Ring
- 4 Nylon Trailing Pin Ring
- 5 Stainless Steel Restraining Ball Ring
- 6 Stainless Steel Spring
- 7 Stainless Steel Shaft Clip
- 8 Stainless Steel Shutter Spring
- 9 NBR O-Ring Seal
- 10 NBR O-Ring Seal
- 11 Stainless Steel Pin
- 12 Stainless Steel Ball
- 13 Nylon Body
- 14 Nylon Sleeve




Flow Rate

CFM (NI/min)


Part No.	87 psi Δ 14.5	87 psi Δ 7.2	87 psi Δ 0 (Exhaust Free)
80220AC	33.55 (950)	24.72 (700)	49.44 (1400)

SAFETY COUPLERS

DN
5.5 mm




1/4 INDUSTRIAL



1:1

80621


MALE SAFETY COUPLER



Part No.	A NPTF	B	C	D	CH
80621-04	1/4	.512 (13)	2.173 (55)	1.200 (30,5)	.748 (19)
80621-06	3/8	.512 (13)	2.173 (55)	1.200 (30,5)	.748 (19)
80621-08	1/2	.669 (17)	2.322 (59)	1.200 (30,5)	.866 (22)

80622


FEMALE SAFETY COUPLER



Part No.	A NPTF	B	C	D	CH
80622-04	1/4	.531 (13,5)	2.165 (55)	1.200 (30,5)	.669 (17)
80622-06	3/8	.531 (13,5)	2.146 (54,5)	1.200 (30,5)	.787 (20)
80622-08	1/2	.689 (17,5)	2.323 (59)	1.200 (30,5)	.945 (24)

621


MALE SAFETY COUPLER



Part No.	A BSPP	B	C	L	CH
621-04	1/4	.512 (13)	2.173 (55)	1.200 (30,5)	.748 (19)
621-06	3/8	.512 (13)	2.173 (55)	1.200 (30,5)	.787 (20)
621-08	1/2	.512 (13)	2.173 (55)	1.200 (30,5)	.984 (25)

622

FEMALE SAFETY COUPLER



Part No.	A BSPP	B	C	L	CH
622-04	1/4	.531 (13,5)	2.165 (55)	1.200 (30,5)	.669 (17)
622-06	3/8	.531 (13,5)	2.146 (54,5)	1.200 (30,5)	.787 (20)
622-08	1/2	.689 (17,5)	2.323 (59)	1.200 (30,5)	.945 (24)

80221AC

1/4 INDUSTRIAL MALE (STEEL)

Part No.	A NPTF	B	C	CH
80221AC-04	1/4	.512 (13)	1.634 (41,5)	.669 (17)
80221AC-06	3/8	.512 (13)	1.634 (41,5)	.748 (19)
80221AC-08	1/2	.669 (17)	1.811 (46)	.866 (22)

HARDENED STEEL




80222AC

1/4 INDUSTRIAL FEMALE (STEEL)

Part No.	A NPTF	B	C	CH
80222AC-04	1/4	.531 (13,5)	1.535 (39)	.669 (17)
80222AC-06	3/8	.531 (13,5)	1.535 (39)	.866 (22)
80222AC-08	1/2	.689 (17,5)	1.693 (43)	.944 (24)

HARDENED STEEL




80223AC

1/4" INDUSTRIAL BARB (STEEL)

Part No.	A	C	D
80223AC-04	1/4	1.713 (43,5)	.472 (12)


HARDENED STEEL



8B121

SAFETY INDUSTRIAL MALE SWIFTFIT


Part No.	A NPTF	B	C	D	CH
8B121-04	1/4 - 18	.512 (13)	3.011 (76,5)	.984 (25)	.827 (21)
8B121-06	3/8 - 18	.512 (13)	3.011 (76,5)	.984 (25)	.827 (21)
8B121-08	1/2 - 14	.669 (17)	3.250 (82,5)	.984 (25)	.984 (25)



8B122

SAFETY INDUSTRIAL FEMALE SWIFTFIT

Part No.	A NPTF	B	C	D	CH
8B122-04	1/4 - 18	.531 (13,5)	2.930 (74,5)	.984 (25)	.827 (21)
8B122-06	3/8 - 18	.531 (13,5)	2.910 (74)	.984 (25)	.827 (21)
8B122-08	1/2 - 14	.689 (17,5)	3.110 (79)	.984 (25)	.944 (24)




BLOW GUNS






TECHNICAL CHARACTERISTICS



361

BLOW GUN WITH STAINLESS STEEL PIPE



Media

- Compressed Air
- Water




Component Parts and Materials

- Technopolymer Body
- Nickel-plated Brass Back Connection
- Nickel-plated Brass Locking Nut
- Stainless Steel AISI 304 Nozzle

Code	L	L1	B
WB361 00 001	90	8.287 (210,5)	7.047 (179)
		min	max
Temperature		- 10 °C (14 F)	+ 80 °C (176 F)
Pressure		12 bar (174 Psi) (1.2 MPa)	
433 NI/min @ 6 bar (87 Psi) - 533 NI/min @ 8 bar (116 Psi)			
LAeq 89 dBA @ 6 bar (87 Psi)			
LAeq 90 dBA @ 8 bar (116 Psi)			
Force on handle		19,8 N @ 6 bar (87 Psi)	
Blowing force		3,7 N @ 6 bar (87 Psi)	
2003/10/CE		Max 85 dBA	3 hr @ 6 bar (87 Psi) 3 hr @ 8 bar (116 Psi)
OSHA 1910.95 (b)		Max 90 dB 8 hr (116 Psi)	

362

BLOW GUN WITH STAINLESS STEEL PIPE



Code	L	L1	B
WB362 00 001	90	8.287 (210,5)	7.303 (185,5)
		min	max
Temperature		- 10 °C (14 F)	+ 80 °C (176 F)
Pressure		12 bar (174 Psi) (1.2 MPa)	
383 NI/min @ 6 bar (87 Psi) - 500 NI/min @ 8 bar (116 Psi)			
LAeq 78 dBA @ 6 bar (87 Psi)			
LAeq 84 dBA @ 8 bar (116 Psi)			
Force on handle		19,8 N @ 6 bar (87 Psi)	
Blowing force		3,4 N @ 6 bar (87 Psi)	
2003/10/CE		Max 85 dBA	8 hr @ 6 bar (87 Psi) 6 hr @ 8 bar (116 Psi)
OSHA 1910.95 (b)		Max 90 dB 8 hr	
OSHA 1910.242 (b)		Max 2,1 bar (30 Psi) when blocked	